
Sequence Language-Independent Type for YAML™ Version 1.1

Working Draft 2005-01-18

Oren Ben-Kiki <oren@ben-kiki.org>
Clark Evans <cce+yaml@clarkevans.com>
Brian Ingerson <ingy@ttul.org>

Copyright © 2001-2005 Oren Ben-Kiki, Clark Evans, Brian Ingerson
This document may be freely copied provided it is not modified.

Status

This specification is a draft reflecting consensus reached by members of the yaml-core mailing list [<http://lists.sourceforge.net/lists/listinfo/yaml-core>]. Any questions regarding this draft should be raised on this list.

1. Sequence

URI:	<code>tag:yaml.org,2002:seq</code>
Shorthand:	<code>!!seq</code>
Kind:	Sequence.
Definition:	Collections indexed by sequential integers starting with zero. Example bindings include the Perl array, Python's list or tuple, and Java's array or vector.
Resolution and Validation:	This tag accepts all sequence values. It is typically used as the fall-back tag for sequence nodes.

Example 1. !!seq Examples

```
# Ordered sequence of nodes
Block style: !!seq
- Mercury # Rotates - no light/dark sides.
- Venus # Deadliest. Aptly named.
- Earth # Mostly dirt.
- Mars # Seems empty.
- Jupiter # The king.
- Saturn # Pretty.
- Uranus # Where the sun hardly shines.
- Neptune # Boring. No rings.
- Pluto # You call this a planet?
Flow style: !!seq [ Mercury, Venus, Earth, Mars, # Rocks
                  Jupiter, Saturn, Uranus, Neptune, # Gas
                  Pluto ] # Overrated
```